

NEW-SURWAY PRODUCT DATASHEET

NVR-6108C NVR System



Housing picture just for your reference, please make real product as standard

MAIN FEATURES

- Support P2P cloud service, including cloud connecting, cloud monitoring, cloud transmitting to access IPC and NVR at anytime and any place;
- All channels image can be displayed simultaneously and main stream display under 4 Split screen mode;
- Recording backup can be accurate to second, Any time period of backup is available;
- Backup recording files in the USB disk can play and search on the NVR directly;
- Support 15X zoom under preview and playback modes;
- NVR assigns IP address for IPC automatically, plug and play (only for the IPC that has private protocol with NVR);
- Support setting IPC parameters on the NVR directly;
- Multi-Language selectable:
English, Spanish, Italian, French, Russian, Persian, Japanese, Chinese, Traditional Chinese, Polish, Thai, Hebrew, Dutch, Kazak
- Support remote view with Windows Mobile Phone (Windows mobile \ Symbian \ Iphone \ Blackberry \ Android)

Technical Specification

Model Number	NVR-6108C
Operating System	Embedded LINUX operating system
Image Code Control	Image code quality adjustable, variable bitstream and constant bitstream optional
Dual Stream	Each channel can set main stream and sub stream
Video Standard	1080P(1920x1080)30fps/960p(1280x960)/720P(1280x720)30fps
Monitoring Image Quality	1080P(1920x1080) /960p(1280x960)/720P(1280x720)
Image Motion Detection	Each screen can set multiple detection areas and set 6-level sensitivity
Recording playback Quality	4ch playback in 4ch 960P/720P mode; 1ch 1080P playback in 1/4ch 1080P mode
Region Cover	Every Channel can set 4 cover regions (IPC Support)
Recording Mode	Support manual, auto, motion detection, alarm trigger record mode
Backup Way	Support U disk, USB mobile HDD, USB DVD-RW, Network storage and backup
Operation Way	Mouse, remote Control front panel

NEW-SURWAY PRODUCT DATASHEET

Local login		User name and password
Recording Storage		Local HDD,network
External ports	Video Input	①8x(1280*720)+sub[640*360]+1Ref.+4Play support 8ch 1MP IP camera
		②8x(1280*960)+sub[640*480]+1Ref.+4Play support 8ch 1.3MP IP camera
		③8x(1920*1080)+sub[640*480]+2Ref.+1Play support 8ch 2MP IP camera
		④8x(720*576)+sub[352*288]+2Ref.+8Play support 8ch 0.4MP IP camera
	Audio Input	8ch network audio input
	Video Output	1ch VGA +1Ch HDMI
	Audio Output	1Ch RCA
	Network Port	1RJ45,10M/100M self-adaptive LAN port
	RS485 Port	/
	USB Port	2 USB 2.0 ports(one on front panel,two on rear panel)
Alarm Input	/	
Alarm Output	/	
Wireless Port	3G,WiFi	
HDD		Mobile HDD/E-SATA /USB Disk
Mobile Surveillance		Support(iPhone,windows Mobile,BlackBerry,Symbian,Android)Smart phone
Power Supply		5V 2A
Power Consumption		≤10W (without HDD)
Working Temperature		-10°C~+55°C
Working Humidity		10%-90%
Dimension		Equipment:88mmx88mmx32mm packing:185.5mmx115.5mmx36mm
Weight(without HDD)		N.W.:105g; With packing:250g
Installation Way		Desktop Installation

The specification is subject to change without notice.